

Incubator series

Large Scale Cell Culture CO₂ Incubator

MCO-80IC-PE



Superior temperature and CO₂ control

- Reach-in design with large 851 litres capacity
- Superior temperature and CO₂ control with rapid recovery times
- Exceptionally low CO₂ consumption rates
- Preventative contamination control




Discovery powered by
precision



MCO-80IC
with optional
inner door kit
(MCO-80ID-PW)

The MCO-80IC is ideal for culturing high volumes of patient samples, performing short-term studies, and working with large volume cell culture apparatus. The MCO-80IC includes Panasonic's advanced incubator technologies such as inCu saFe® interior, UV decontamination option and solid-state infrared CO₂ sensor with P.I.D. control to provide outstanding performance and anti-contamination control.

The incubator also features exceptionally low CO₂ gas consumption for economic operation.



Horizontal
laminar
airflow
system

Superior Temperature and CO₂ Control

● Horizontal laminar airflow system

The MCO-80IC features a cross-shelf horizontal airflow system, which promotes optimum temperature and CO₂ uniformity throughout the incubator and contributes to rapid recovery after door openings. The conditioned air is directed evenly through the incubator using perforated wall plenums made from Panasonic's exclusive inCu saFe® copper-enriched stainless steel. The horizontal airflow helps to maintain uniform air circulation and even temperature distribution when samples are placed in the incubator.

● P.I.D. temperature control

Limits temperature fluctuation to $\pm 0.1^{\circ}\text{C}$.

● Infrared (IR) CO₂ sensor with P.I.D. microprocessor control

Delivers precise control and fast CO₂ recovery characteristics.

● Exceptionally low CO₂ gas consumption rates

Less than half of a similar competitor unit.

Flexibility and Ease of Use


- Large capacity, 851 litre CO₂ incubator with adjustable shelving provides flexibility in use.
- Accommodates roller bottle apparatus, 5 bottles wide x 7 bottles high (requires optional Mounting Ramp Kit, MCO-80RBS).
- Full view, double paned glass door allows clear observation of cultured samples.
- Large LED digital display and keypad for greater visibility and ease of set-up.



Control Panel	Panasonic MCO-80IC			Competitor Model		
Door Openings (Number per day)	0	2 x 30 sec	2 x 60 sec	0	2 x 30 sec	2 x 60 sec
CO ₂ Consumption (litres per day)	280 l/day	440 l/day	457 l/day	597 l/day	728 l/day	752 l/day
30kg CO ₂ Cylinder Retention Time*	60 days	39 days	37 days	28 days	23 days	23 days

* Test conditions: Set temperature = 37°C, set CO₂ = 5%, Ambient temperature = 20°C.

* All values are actual test values for reference only, and cannot be guaranteed in operation.



- Frame heater
- Door glass heater
- Door frame heater

Preventative Contamination Control

- Incubator interior and plenums made from Panasonic's exclusive inCu saFe[®] germicidal, copper-enriched stainless steel.
- Heated glass door and door frame heater prevent condensation.
- Optional UV sterilisation system for humidity reservoir.

CO₂ Control - Faster Recovery & Lower Gas Consumption

Panasonic's large scale cell culture incubator has been designed specifically for critical applications in pharmaceutical, biotechnology and clinical investigation.

Large chamber capacity applications require special consideration of gas usage and recovery times.

Panasonic's proprietary IR sensor with P.I.D. CO₂ control algorithm is paramount to the industry's leading design.

An optional inner door system (MCO-80ID) is also available to enhance these results further.

Humidity Selection and Optional UV Sterilisation


As standard, the MCO-80IC offers a choice of normal and high humidity modes for different application needs. For reliability and reduced maintenance the humidity reservoir heater is located on the outside wall of the reservoir and is not susceptible to corrosion or scaling through contact with water. An optional auto-fill 20 litre secondary water tank (Model MCO-80AS) provides an additional water supply to the humidity reservoir.

Panasonic's patented and laboratory proven SafeCell UV sterilisation system (option) is employed to sterilise the humidifying water reservoir and help minimise contamination concerns.


Large Scale Cell Culture CO₂ Incubator MCO-80IC-PE

The MCO-80IC is ideal for culturing high volumes of patient samples, performing short-term studies, and working with large volume cell culture apparatus.


Temperature level recovery after a 30 second door opening for the Panasonic MCO-80IC




CO₂ Recovery after a 60 second door opening for the Panasonic MCO-80IC.



CO₂ Recovery after a 60 second door opening for the competitor model.



Dimensions



CO₂ reach-In Incubator

Characteristics

PUF = Rigid polyurethane foamed insulation
V = Visual alarm
B = Buzzer alarm
R = Remote alarm



MODEL		MCO-80IC-PE
Dimensions		
External dimensions (W x D x H)	mm	986 x 853 x 2040
Internal dimensions (W x D x H)	mm	806 x 693 x 1524
Volume	ltr	851
Net weight	kg	275
Technical Data		
Power supply	V	230
Frequency	Hz	50
Noise Level ¹⁾	dB	33
Insulation material		PUF
Performance		
Temperature sensor		Thermistor
CO ₂ sensor		IR
Temp control range and fluctuation	°C	Ambient temp. +5 to 50 [AT; 20°C to 35°C]
Temperature uniformity	°C	±0.5 ²⁾
CO ₂ control range and fluctuation	%	0 ~ 20, ±0.15
Humidity control range and fluctuation	%RH	Normal mode; >80% R.H. High mode; > 90% R.H.
Alarms		
Power failure		R
Out of temperature setting		V-B-R
High temperature		V-B-R
Out of CO ₂ setting		V-B-R
Door open		V
Water level		V
General		
Exterior material		Painted steel
Colour (exterior)		Bio-gray
Cabinet material (interior)		SS copper alloyed
Outside door		1 double paned glass
Reversible door	qty	Y
Inside door		Option
Outside door lock	qty	N
Shelves		5
Max. load per shelf	qty	30
Max. total load	kg	150
Max. Shelf capacity	kg	5
Access port		2
- position	qty	One on each side
- diameter	Ø mm	40
CO₂ Incubator Contamination Control & Operating Systems		
H ₂ O ₂ decontamination system (option)		N
SafeCell® UV system (option)		Y
InCu saFe®		Y
Water level sensor		Y
DHA heating system		N (laminar airflow)
CO₂ Incubator options		
Shelves and brackets (InCu saFe®)		MCO-80ST-PW
CO ₂ -gas pressure regulator		MCO-100L-PW
Automatic CO ₂ switchover system		MCO-80GC-PW
UV-system kit		MCO-80UVS-PE
Inner door with 4 small doors		MCO-80ID-PW (5 small doors)
Digital interface		MTR-480-PW
Analogue interface		MCO-420MA-PW
Roller bottle rack mounting kit		MCO-80RBS-PW
Automatic water supply system kit		MCO-80AS-PW

notes: ¹⁾ Nominal Value
²⁾ ±0.25°C; ambient temp 25°C, settings 37°C, CO₂ 5%, O₂ 5% (Multigas), no load

Appearance and specification are subject to change without notice.

Panasonic

for more online information:

www.biomedical.panasonic.eu