

300-Series Medical Device Dryers

Cenorin's line of custom configured drying cabinets efficiently process a variety of medical devices and equipment. The 300 Series is comprised of two models, the 330 (with a solid back) and the 340 (with a back door, or "pass-through"). Both offer a wide variety of options and accessories tailored to meet your specific reprocessing needs.

- Large interior volume and a modular design permitting multiple device types and sizes, such as surgical trays, containers, various tubing sizes, anesthesia bags, croupettes, aerosol generators, endoscopes, laryngoscope blades, circuits, CPAP masks and any and all miscellaneous parts
- Clear composite doors swing 180° for easy loading and unloading
- Low maintenance and ease of use
- Robust construction with stainless steel components
- Tubing, Bag and Bottle drying fixtures, Half-width shelves or full-width shelves may be added
- Programmable user interface with temperature and cycle time selection, and automatic filter change alert
- Highest air circulation in the industry, resulting in faster drying times when configured with HEPA filter and tube drying rack

Warranty

Two year warranty covers 100% of parts and labor, with an optional 5-year Extended Warranty Plan (parts only) available. Toll-free technical assistance for the lifetime of the equipment. Warranty service is provided through Medical Equipment Repair Association (MERA) or through in-house biomedical staff.



Model 330 Configuration with Half-Width Shelving Option



Model 340 Configuration with Half-Width Shelving Option

ThermaSure 300-Series Dryer

Controls

- Microprocessor controls for cycle timing and temperature processes; visual signal when the cycle is complete
- Display continuously shows cycle status, time remaining, and cabinet temperature
- Visual alert when HEPA filter needs to be replaced
- Cycle options includes a TIMED DRY cycle or a CONTINUOUS DRY

Options

- HEPA Filter 99% of particles 0.3 microns and greater (standard configuration comes with a Superfine Filter - 85-90% of particles 3.0 microns and greater).
- Bag & Bottle Drying Rack holds up to 12 devices
- Tube Drying Rack stationary, capacity is 84 tubes, accepts up to 2-1/2" diameter tubes
- Half-Width Stainless Shelves 14.2" x 20.5"; holds up to 18 shelves; each shelf bears up to 40lbs
- Full-Width Stainless Shelves 33.38" x 20"; holds up to 9 shelves; each shelf bears up to 80lbs
- Stainless Small Parts Handling Tray 10 -3/8" x 19-3/4" x 1"; can hold up to 18 trays



Model 330 with Half-Width Shelving and Bag & Bottle Rack Options

Model 330 with Half-Width Shelving and



Model 340 with Maximum Full-Width Shelving Option

Model 340 with Half-Width & Full-Width Shelving Option and Small Parts Trays Options

ThermaSure 300-Series Dryer - Technical Specifications

PHYSICAL SPECIFICATIONS		
MODEL:	330 – DOUBLE FRONT 340 – DOUBLE FRONT,	
	DOUBLE BACK	
WIDTH:	36" (91 cm)	
DEPTH:	26.5" (67 cm)	
HEIGHT:	85" (216 cm)	
WEIGHT:	475 lbs (215 kg)	
(W/ HEPA FIILTER):	488 lbs (221 kg)	
VOLUME:	29 ft ³ (.82 m ³) (Interior)	
*Add 2" to noted dimension for power cord clearance		

CONSTRUCTION OR SUFICIALISMS			
CONSTRUCTION SPECIFICATIONS			
DOORS:	CLEAR PLASTIC SINGLE PANEL		
CABINET:	16 GAUGE STEEL		
BASE:	14 GAUGE STAINLESS STEEL		
FINISH/PAINT:	BAKED POWDER COAT		
CONTROLS	MICROPROCESSER BASED		
INSULATION:	1" POLYSTYRENE FOAM		

PERFORMANCE SPECIFICATIONS				
	120 V	240 V		
MEAN CABINET TEMP:	130-140°F (54-60°C)			
EXHAUST:	7370 BTU/HR	8189 BTU/HR		
EXHAUST W/ HEPA:	7780 BTU/HR	9008 BTU/HR		

ELECTRICAL SPECIFICATIONS				
VOLTAGE (± 10%)	120 V	240 V		
CYCLES:	60 HZ	60 HZ		
CURRENT/WATTS:	18 A/ 2160 W	10 A/ 2400 W		
CURRENT W/ HEPA/WATTS:	19 A/ 2280 W	11 A/ 2640 W		
CIRCUIT REQ'D:	120 V, 30 A	240 V, 30 A		
	DEDICATED	DEDICATED		
	CIRCUIT W/	CIRCUIT W/		
	LOCKING	LOCKING		
	RECEPTACLE	RECEPTACLE (NEMA		
	(NEMA L5-30R)	L6-30R)		
EQUIPPED W/:	10' (305 cm)	10' (305 cm)		
	10/3 SJO CORD &	10/3 SJO CORD &		
	30 A HOSPITAL	30 A HOSPITAL		
	GRADE PLUG	GRADE PLUG		
	(NEMA L5-30P)	(NEMA L6-30P)		
CERTIFICATIONS:	#224861 constant #224861			

Cenorin, LLC • 6324 South 199th Place • Suite 107 • Kent, WA 98032 Phone: 253-395-2400 • Fax: 253-395-2650 • Toll Free: 1-800-426-1042

TS SLSFRM 16 Rev.F Controlled